


# SAFETY DATA SHEET

## SECTION 1 – IDENTIFICATION: PRODUCT IDENTIFIER/CHEMICAL IDENTITY

- 1.1 PRODUCT IDENTIFIER:** Stihl MotoMix
- 1.2 PRODUCT CODE:**  
1L can 7004 874 0102  
4L can 7004 874 0103  
60L drum 7004 874 0104  
205L drum 7004 874 0105
- 1.3 RELEVANT IDENTIFIED USES OF THE MIXTURE AND USES ADVISED AGAINST:**  
**RELEVANT IDENTIFIED USES:** Hydrocarbon mixture to be used as a special fuel for 2 stroke engines.  
**RESTRICTIONS ON USE:** None known.
- 1.4 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET:**  
**SUPPLIER NAME:** Stihl Pty Ltd (ABN: 76 004 881 145)  
**ADDRESS:** 5 Kingston Park Court, Knoxfield, Victoria, Australia, 3180  
9 Bishop Browne Place, East Tamaki, Auckland, New Zealand, 1730.  
**E-MAIL:** [csc@stihl.com.au](mailto:csc@stihl.com.au); [info@stihl.co.nz](mailto:info@stihl.co.nz)  
**TELEPHONE NUMBER:** +61 3 9215 6666 (NZ: +64 9262 4000)
- 1.5 EMERGENCY TEL. NUMBER:** Poisons Information Centre (Aust 131 126; NZ 0800 764 766)
- 1.6 HSNO DETAILS:**  
**HSNO APPROVAL NUMBER:** HRC000003.  
**HSNO APPROVAL NAME:** Petrol (Unleaded).

## SECTION 2 – HAZARD(S) IDENTIFICATION

- 2.1 CLASSIFICATION OF THE HAZARDOUS CHEMICAL:**  
**GHS CLASSIFICATION HAZARD CLASS & CATEGORY:** The product is a mixture and has been assessed under the Model Work Health and Safety Regulations with the following Classification:  
Flammable Liquids Category 1  
Skin Corrosion/Irritation Category 2  
Aspiration Hazard Category 1  
Specific Target Organ Toxicity Single Exposure Category 3  
Chronic Aquatic Toxicity Category 2
- 2.2 LABEL ELEMENTS INCLUDING PRECAUTIONARY STATEMENTS:**  
**SIGNAL WORD:** Danger.
- PICTOGRAMS:**  

- HAZARD STATEMENTS:**  
H224 - Extremely flammable liquid and vapour.  
H304 - May be fatal if swallowed and enters airways.  
H315 - Causes skin irritation.  
H336 - May cause drowsiness or dizziness.  
H411 - Toxic to aquatic life with long lasting effects.

# SAFETY DATA SHEET

## SECTION 2 – HAZARD(S) IDENTIFICATION Continued

### PRECAUTIONARY STATEMENTS:

#### PREVENTION:

P102 - Keep out of reach of children.  
P103 - Read label before use.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground and bond container and receiving equipment.  
P241 - Use explosion-proof electrical/ventilating/lighting equipment.  
P242 - Use non-sparking tools.  
P243 - Take action to prevent static discharges.  
P261 - Avoid breathing mists/vapours/spray.  
P264 - Wash hands thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection/Hearing protection.

#### RESPONSE:

P101 - If medical advice is needed, have product container or label at hand.  
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTRE/doctor/physician.  
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340 - IF INHALED: Remove victim to fresh air and keep comfortable for breathing.  
P312 - Call a POISON CENTRE/doctor/physician if you feel unwell.  
P331 - Do NOT induce vomiting.  
P332+P313 - If skin irritation occurs: Get medical advice/attention.  
P362 + P364 - Take off contaminated clothing and wash it before reuse.  
P370+P378 - In case of fire: Use dry powder, foam or water spray for extinction.  
P391 - Collect spillage.

#### STORAGE:

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P235 - Keep cool.  
P405 - Store locked up.

#### DISPOSAL:

P501 - Dispose of contents/container in accordance with local regulations.

#### 2.3 OTHER HAZARDS:

The vapours may have a narcotic effect as well as lead to drowsiness and dizziness. Excessive exposure may result in irritation to the respiratory system as well as possible irritation to the eye. Due to the mixture of hydrocarbon solvents there is a possibility that repeated exposure may cause skin dryness or cracking. People with pre-existing skin conditions, such as eczema or dermatitis, should take precautions so as not to exacerbate the condition. The product will potentially form flammable/explosive mixtures in air. There may be static discharge issues with the product in large scale operations that could lead to a fire. As for all chemical products, persons should not expose open wounds, cuts, abrasions or irritated skin to this material.

# SAFETY DATA SHEET

## SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENTS	CAS NUMBER	Concentration % W/W	GHS Classification
Naphtha, petroleum, full range alkylate, butane containing	68527-27-5	> 50%	Flam Liq 1 - H224 Asp Haz 1 - H304 Skin Irrit 2 - H315 STOT SE 3 - H336 Chron Aq Tox 4 - H413
Butane, 2-methyl- (isopentane)	78-78-4	10% - 25%	Flam Liq 1 - H224 Asp Haz 1 - H304 STOT SE 3 - H336 Chron Aq Tox 2 - H411 AUH066
Heptane, 2,2,4,6,6 - pentamethyl	13475-82-6	10% - 25%	Flam Liq 3 - H226 Asp Haz 1 - H304 Chron Aq Tox 4 - H413 AUH066

Not Applic = Not Applicable \* Please see Section 15 of this SDS for the full text description of the Label Elements.  
The product contains: Benzene <0.05 Vol%; n-hexane <0.5 Vol%; Aromatics <0.5 Vol%; Olefins <0.5 Vol%.

## SECTION 4 – FIRST AID MEASURES

### 4.1 DESCRIPTION OF NECESSARY FIRST AID MEASURES:

- INGESTION:** Rinse mouth out with water. If swallowed, do NOT induce vomiting. For advice, contact the Poisons Information Centre (phone Australia 131 126; New Zealand 0800 764 766) or a doctor at once. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Within 6 hours of ingestion, if delayed symptoms, such as a fever greater than 38.3°C, shortness of breath, chest congestion or continued coughing/wheezing occurs transport immediately to a medical facility. As the product is hydrocarbon based and of low viscosity, if ingested seek urgent medical assistance.
- EYE:** If in eyes, hold eyelids apart and flush the eye immediately with large amounts of running water. Continue flushing for at least 15 minutes or until advised to stop by a doctor. Check for contact lenses. If there are contact lenses, these should be removed after several minutes of rinsing by the exposed person or medical personnel if it can be done easily. After flushing, if irritation develops or persists, seek medical assistance.
- SKIN CONTACT:** If skin or hair contact has occurred remove any contaminated clothing and footwear, wash skin or hair thoroughly with soap and water. As the product is rated as a skin irritant, after washing if skin irritation occurs, it is recommended that you seek medical advice/attention taking this Safety Data Sheet with you.
- INHALATION:** If affected, remove the patient from further exposure into fresh air, if safe to do so. If providing assistance, avoid exposure to yourself - only enter contaminated environments with adequate respiratory equipment, once environment has been assessed for flammable vapours. Once removed, lay patient down in a well-ventilated area and reassure them whilst waiting for medical assistance. If symptoms, such as dizziness or uncoordination occur, seek immediate medical assistance. If not breathing, provide artificial respiration and seek immediate medical assistance. If unconscious, place in a recovery position and seek immediate medical assistance. If irritation develops or persists, consult a doctor.

# SAFETY DATA SHEET

## SECTION 4 – FIRST AID MEASURES Continued

### PROTECTION FOR FIRST AIDERS:

No person shall place themselves in a situation that is potentially hazardous to themselves. Assess the scenario for PPE requirements before entering. Assess environment for flammable vapours before entering. Never enter an environment with a flammable atmosphere. Do not enter contaminated area without a respirator or Self Contained Breathing Apparatus once you have assessed the atmosphere. As the product is hydrocarbon based and of low viscosity, if the person has ingested the product, do not use direct mouth-to-mouth resuscitation techniques. Always ensure that you are wearing gloves when dealing with first aid procedures involving chemicals and/or blood.

### FIRST AID FACILITIES:

Eye wash fountain and safety showers, or at least a source of flowing water, are recommended in the area where the product is used.

### 4.2 MOST IMPORTANT SYMPTOMS & EFFECTS, BOTH ACUTE & DELAYED, CAUSED BY EXPOSURE:

#### ACUTE:

The product is rated as a skin irritant by calculation. Skin contact may lead to redness or itching. Vapours may cause drowsiness or dizziness. Inhalation of high vapour concentrations may cause central nervous system depression resulting in dizziness, headache, nausea and possible loss of coordination. Ingestion or inhalation of vapours may lead to irritation of the mouth and respiratory tract. Symptoms may include a burning sensation in the nose and throat, coughing or difficulty breathing. Ingestion may lead to nausea and diarrhoea. The product is an aspiration hazard. If material is aspirated into the lungs it may exhibit as coughing, wheezing, congestion or fever. Eye contact may lead to localised burning, redness, pain, swelling and tearing.

#### CHRONIC:

Repeated or prolonged skin contact may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. Skin contact may aggravate/exacerbate existing skin conditions, such as dermatitis.

### 4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NECESSARY:

#### ADVICE TO DOCTOR:

Treat symptomatically. As the product is hydrocarbon based and of low viscosity, if vomiting has occurred after ingestion, the patient should be monitored for adverse effects to ensure that the product has not aspirated into the lungs. Small amounts of this product aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary oedema. Inhalation of high vapour concentrations may cause central nervous system depression.

## SECTION 5 – FIRE FIGHTING MEASURES

### 5.1 EXTINGUISHING MEDIA:

#### SUITABLE MEDIA:

Use extinguishing media appropriate for surrounding fire. Use carbon dioxide, foam, dry chemical or water spray. Spray down fumes resulting from fire.

#### UNSUITABLE MEDIA:

Avoid using full water jet directed at residual material that may be burning. Water may cause splattering on hot residues. Product will float on water.

### 5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:

#### COMBUSTION HAZARDS:

Combustion may produce oxides of carbon, as well as smoke and irritating vapours.

# SAFETY DATA SHEET

## SECTION 5 – FIRE FIGHTING MEASURES Continued

### 5.3 ADVICE FOR FIREFIGHTERS:

**FIRE:** This product is extremely flammable with a typical flash point of -56°C. The vapour is heavier than air and will spread along the ground and may accumulate in low points or depressions. Therefore, ignition may occur well away from the point of release of the material. Keep storage tanks, pipelines, fire exposed surfaces, etc. cool with water spray.

**HAZCHEM CODE:** 3YE.

**EXPLOSION:** No information to indicate that the product is an explosion hazard; though the solvent component will form an explosive mixture with air. NOTE: Under the WHS legislation, this product is rated as Flammable Liquid - Category 1, with a typical Flash point of -56°C. Extinguish all sources of flame or spark. Closed containers may explode when exposed to extreme heat.

**PROTECTIVE EQUIPMENT:** In the event of a fire, wear full protective clothing and self-contained breathing equipment with full-face piece operated in the pressure demand or other positive pressure mode.

## SECTION 6 – ACCIDENTAL RELEASE MEASURES

### 6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

**PERSONAL PROTECTION:** For small spills, wear Nitrile gloves, glasses/goggles, boots and full-length clothing. During routine operation for a small spill in the open a respirator is not required. However, if mists or vapours are generated, an approved organic vapour/particulate respirator is required. For large spills, or in confined spaces, a full chemically resistant body-suit is recommended and the atmosphere must be evaluated for oxygen deficiency and whether the atmosphere is flammable. If in doubt about potential oxygen deficiency, wear self-contained breathing apparatus. Never enter an environment with a flammable atmosphere.

**CONTROL MEASURES:** Ventilate area and extinguish and/or remove all sources of ignition. CAUTION: Vapour may form an explosive mixture with air. Never enter a spill area unless you know the vapours have dissipated to make the area safe. Stop the leak if safe to do so. Caution: The spilled product will be slippery. Avoid contact with the spilled material.

**EMERGENCY PROCEDURES:** In the event of a spill or accidental release, notify the relevant authorities in accordance with all applicable regulations.

### 6.2 ENVIRONMENTAL PRECAUTIONS:

**SPILL ADVICE:** Do not allow product to enter drains, surface water, sewers or watercourses - inform local authorities if this occurs. Take precautions against static discharge. Ensure all equipment is grounded and use non-sparking tools during clean up operations.

### 6.3 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP:

**CONTAINMENT:** Contain the spill and absorb with a proprietary absorbent material, sand or earth. Caution: The spilled product will be slippery. Be careful of static discharges and/or sparking during clean up. For large spills prepare a bund/barrier/dyke ahead of the spill to confine the spill and allow later recovery. If there is the possibility of spills to enter drains, surface water, sewers or watercourses ensure bunding, or that drains are covered, to minimise the potential for this to occur.

# SAFETY DATA SHEET

## SECTION 6 – ACCIDENTAL RELEASE MEASURES Continued

**CLEANING PROCEDURES:** Having contained the spill, as mentioned above, collect all material quickly and place used absorbent in suitable containers. Be careful of static discharges and/or sparking during clean up. Use only non-sparking tools during cleaning operations. **CAUTION:** The spilled product will be slippery. Follow local regulations for the disposal of waste. For large spills that have been banded, the material can be pumped, using flammable liquid equipment, into vessels and returned for reprocessing or destruction. Personnel must wear the appropriate clothing as required in Section 6.1 during cleaning procedures; after the environment has been evaluated. Wash contaminated area and objects with detergent and water after spill has been cleared. Rinse the cleaned area with water. Do not allow wash water or rinsings to enter drains, surface water, sewers or water courses.

## SECTION 7 – HANDLING AND STORAGE, INCLUDING HOW THE CHEMICAL MAY BE SAFELY USED

### 7.1 PRECAUTIONS FOR SAFE HANDLING:

#### SAFE HANDLING:

Avoid contact with the product by using appropriate protective equipment such as gloves, glasses or goggles and full-length clothing. Extinguish any potential sources of ignition before using as flammable vapours will be generated during application. Do not leave containers in direct sunlight. Due to the possibility of pressure build up in the container, open the container with care. Avoid breathing mists or vapours. Do not smoke when handling the material. Prevent small spills and leakage to avoid slip hazards. Properly dispose of any contaminated rags or cleaning materials in order to prevent fire hazards. Eating, drinking, and smoking should be prohibited in the area where this material is handled, stored and processed. Workers should follow good personal hygiene practices, such as washing hands before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Keep containers tightly closed when not in use. Please note that flammable mixtures may be formed when residual material remains in empty containers. Prevent product from entering waterways, drains or sewers. There is the potential for electrostatic accumulation in the product. As a precaution, containers should always be earthed before dispensing commences.

### 7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:

#### SAFE STORAGE:

This is a hydrocarbon based Class 3 Flammable Liquid (FP= -56°C). Store in a cool, dry, well ventilated area away from direct sunlight, ignition sources, oxidising agents, foodstuffs and clothing. Dangerous Goods Storage and Handling Regulations must be considered when storing this material. Keep containers closed when not in use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store only in original containers. It is recommended that the product is stored below 25°C.

#### INCOMPATIBILITIES:

Oxidising substances including strong acids. Light naphtha solvents are often not compatible with natural rubber, butyl rubber, EPDM rubber and polystyrene. Ensure that the material remains in the original container whenever possible.

# SAFETY DATA SHEET

## SECTION 8 – EXPOSURE CONTROLS & PERSONAL PROTECTION

### 8.1 EXPOSURE CONTROL MEASURES:

**EXPOSURE LIMIT VALUES:** Exposure standards for the product have not been established. The following values are applicable for the individual components:

**Petrol (Gasoline):**

TWA: 900 mg/m<sup>3</sup>

**Butane, 2-methyl- (isopentane):**

TWA: 600 ppm 1800 mg/m<sup>3</sup> (HSE - WEL)

### 8.2 BIOLOGICAL MONITORING:

No data available.

### 8.3 CONTROL BANDING:

No data available.

### 8.4 ENGINEERING CONTROLS:

**ENGINEERING CONTROLS:** Local ventilation is recommended to minimise the potential for exposure and for the build up of flammable vapours. In the operation of certain equipment, at elevated temperatures, or in confined spaces mists or vapour may be generated and local exhaust ventilation should be provided to avoid the build up of flammable vapours, as well as maintain airborne concentration levels below the nominated exposure standard and at an acceptable level that does not cause irritation. Please note: Due to the flammable nature of the product, if there is a necessity to use ventilation equipment it should not be a potential source of ignition for any vapours generated.

### 8.5 INDIVIDUAL PROTECTION MEASURES:

**EYE & FACE PROTECTION:** Wear safety glasses/goggles to avoid eye contact when refilling operations are occurring. If there is a risk of splashing during use, a full face shield is recommended. Use eye protection in accordance with AS 1336 and AS 1337.

**SKIN (HAND) PROTECTION:** If there is the chance of contact with the material wear gloves to provide hand protection. Nitrile gloves are recommended.

### SKIN (CLOTHING) PROTECTION:

During normal operating procedures, long sleeved clothing is recommended to avoid skin contact. Soiled clothing should be washed with detergent prior to re-use.

**RESPIRATORY PROTECTION:** During routine operation a respirator is not required. However, if mists or vapours are generated, an approved half face organic vapour/particulate respirator is required. Use respirators in accordance with AS 1715 and AS 1716.

**THERMAL PROTECTION:** Not applicable.

# SAFETY DATA SHEET

## SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 PHYSICAL AND CHEMICAL PROPERTIES:

<b>APPEARANCE:</b>	Green liquid.
<b>ODOUR:</b>	Characteristic solvent-like.
<b>ODOUR THRESHOLD:</b>	No data available.
<b>pH:</b>	Not applicable.
<b>MELTING/FREEZING POINT:</b>	No data available.
<b>INITIAL BOILING POINT:</b>	< 35°C.
<b>BOILING RANGE (°C):</b>	Typically < 35°C - 180°C.
<b>FLASHPOINT (°C):</b>	Typically -56°C
<b>EVAPORATION RATE:</b>	No data available.
<b>FLAMMABILITY LIMITS (%):</b>	Lower: 1.1%; Upper: 6.0%.
<b>VAPOUR PRESSURE (kPa):</b>	< 95kPa @ 50°C.
<b>VAPOUR DENSITY:</b>	No data available.
<b>DENSITY (g/mL @ 20.0°C):</b>	Typically 0.69.
<b>SOLUBILITY IN WATER(g/L):</b>	Not miscible in water.
<b>PARTITION COEFFICIENT:</b>	No data available for the product.
<b>AUTO-IGNITION TEMP (°C):</b>	Naphtha component 280-470°C; 2,2,4,6,6-pentamethylheptane 410°C, and isopentane 420°C.
<b>DECOMPOSITION TEMP (°C):</b>	No data available.
<b>VISCOSITY (cSt @ 100°C):</b>	No data available.
<b>VISCOSITY (cSt @ 40°C):</b>	No data available.
<b>VISCOSITY (cSt @ 20°C):</b>	No data available.

## SECTION 10 – STABILITY AND REACTIVITY

<b>10.1 REACTIVITY:</b>	The product does not pose any further reactivity hazards other than those listed in the following sub-sections. With its low Flash Point the product may form explosive mixtures with air at room temperature.
<b>10.2 CHEMICAL STABILITY:</b>	Stable under recommended storage and handling conditions (see section 7).
<b>10.3 POSSIBILITY OF HAZARDOUS REACTIONS:</b>	Keep away from strong oxidising agents, such as strong acids, chlorates, nitrates and peroxides. Hazardous polymerisation does not occur.
<b>10.4 CONDITIONS TO AVOID:</b>	This product has a typical flash point of -56°C. Avoid ignition sources including heat and sparks. Observe the usual precautionary measures for handling chemicals. Do not heat the container or leave the container open when not in use.
<b>10.5 INCOMPATIBLE MATERIALS:</b>	Strong oxidising agents including concentrated acids. Light naphtha solvents are often not compatible with natural rubber, butyl rubber, EPDM rubber and polystyrene.
<b>10.6 HAZARDOUS DECOMPOSITION PRODUCTS:</b>	Hazardous decomposition products are not expected to form during normal storage requirements. See Section 5.2 for Hazardous Combustion products.

## SECTION 11 – TOXICOLOGICAL INFORMATION

### 11.1 INFORMATION ON TOXICOLOGICAL EFFECTS:

The product is a mixture and test data is not available for the product as a whole. However, based on information of ingredients, the manufacturer has nominated the following for the product components:

**Butane, 2-methyl- (isopentane):**

Oral - LD<sub>50</sub> (Rat): >2,000 mg/kg

Inhalation - LC<sub>50</sub> (Rat, vapour, 4 hours): >25.3 mg/L

**2,2,4,6,6-pentamethylheptane:**

Oral - LD<sub>50</sub> (Rat): >5,000 mg/kg



# SAFETY DATA SHEET

## SECTION 11 – TOXICOLOGICAL INFORMATION Continued

- 11.2 SWALLOWED:** This product is expected to have a low order of toxicity associated with it when ingested. It may cause slight irritation to the mouth, throat and digestive tract. The hydrocarbon component means this is a Schedule 5 Poison. As the product is hydrocarbon based and the viscosity is low, caution should be taken in respect to aspiration into the lungs. Small amounts of this product aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary oedema. Ingestion of large amounts may lead to nausea and vomiting. During normal usage ingestion should not be a means of exposure.
- 11.3 SKIN CORROSION/ IRRITATION:** This product is rated as Causes skin irritation. Prolonged or repeated contact may cause defatting of the skin which may lead to dermatitis. Correct handling procedures incorporating appropriate protective clothing and gloves should minimise the risk of skin irritation. People with pre-existing skin conditions, such as dermatitis, should take extreme care so as not to exacerbate the condition.
- 11.4 SERIOUS EYE DAMAGE/ IRRITATION:** This product is not expected to exhibit Eye Irritation or Serious Damage/ Corrosivity, based on the available data and the known hazards of the components. May be mildly irritating to the eyes. Symptoms may include localised burning, redness and tearing. Correct handling procedures incorporating appropriate eye protection should minimise the risk of eye irritation.
- 11.5 RESPIRATORY OR SKIN SENSITISATION:** This product is not expected to be a skin sensitiser, based on the available data and the known hazards of the components. This product is not expected to be a respiratory tract sensitiser, based on the available data and the known hazards of the components.
- 11.6 GERM CELL MUTAGENICITY:** The product is not expected to be a mutagenic, based on the available data and the known hazards of the components. Long term animal experiments have shown that any health risks in these types of materials are associated with the level of benzene in the product. This is removed during the manufacturing process to a level at which no health risks are expected as a result of normal handling.
- 11.7 CARCINOGENICITY:** The product is not expected to be a carcinogen, based on the available data and the known hazards of the components. Long term animal experiments have shown that any health risks in these types of materials are associated with the level of benzene in the product. This is removed during the manufacturing process to a level at which no health risks are expected as a result of normal handling.
- 11.8 REPRODUCTIVE TOXICITY:** This product is not expected to be a reproductive hazard, based on the available data and the known hazards of the components.
- 11.9 SPECIFIC TARGET ORGAN TOXICITY (STOT) - SINGLE EXPOSURE:** There is no data available for the product as a whole. However, based on the available data and the known hazards of the components this product is rated as may cause drowsiness or dizziness. It contains volatile hydrocarbon components, hence inhalation of vapours or mist may cause irritation to the nose and throat. Inhalation of high concentrations or ingestion of the product may have a narcotic effect causing central nervous system depression resulting in drowsiness, headaches, dizziness and nausea. Exposure to high levels of hydrocarbon solvent vapours may impact on the liver and kidneys. Continued inhalation of high concentration levels may result in unconsciousness and/or death.
- 11.10 SPECIFIC TARGET ORGAN TOXICITY (STOT) - REPEATED EXPOSURE:** There is no data available for the product as a whole. This product is not expected to cause organ damage from prolonged or repeated exposure, based on the available data and the known hazards of the components.

# SAFETY DATA SHEET

## SECTION 11 – TOXICOLOGICAL INFORMATION Continued

**11.11 ASPIRATION HAZARD:** This product is rated as an aspiration hazard - May be fatal if swallowed and enters airways. Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary oedema. This can be fatal. As the product is hydrocarbon based, if the product has been ingested or vomiting has occurred after ingestion, the patient must seek urgent medical attention and should be monitored for adverse effects.

**11.12 OTHER INFORMATION:** Data indicates that exposure to very high levels of light solvent materials have been associated with irregular heart rhythms and cardiac arrest.

## SECTION 12 – ECOLOGICAL INFORMATION

**12.1 ECOTOXICITY:** There is no data available for the product as a whole. The manufacturer nominates the following Ecotoxicity data:

**Butane, 2-methyl- (isopentane):**

EC<sub>50</sub> (Daphnia magna, 48 hr): 2.3 mg/L.

LC<sub>50</sub> (Reg, 96hr): 3.1 mg/L.

Based upon calculated values, according to the manufacturer, the overall product is expected to be rated as Toxic to aquatic life with long lasting effects.

**12.2 PERSISTENCE &  
DEGRADABILITY:**

There is no data available for the product as a whole.

**12.3 BIOACCUMULATIVE  
POTENTIAL:**

There is no data available for the product as a whole.

**12.4 MOBILITY IN SOIL:**

There is no data available for the product as a whole. The product contains volatile components which will evaporate into the air if released to the environment. Large volumes may penetrate soil and could contaminate groundwater.

**12.5 OTHER ADVERSE  
EFFECTS:**

There is no data available for the product as a whole. The product floats on water and contains volatile components which will evaporate into the air if released to the environment.

## SECTION 13 – DISPOSAL CONSIDERATIONS

**13.1 DISPOSAL METHODS:  
PRODUCT:**

The product should not be released to the environment, so any unused material should be recycled wherever possible or be disposed of as hazardous waste at an appropriate collection depot. The product is also suitable for incineration at very high temperatures to prevent formation of undesirable combustion products. Spilled product that cannot be recovered should be absorbed and then shovelled into a suitable waste container, such as a plastic drum and then be treated as a solid waste. Follow Government regulations for disposal of such waste. All unused, waste or spilled product must be taken for recycling or disposal by suitably licensed contractors in accordance with Government regulations. Note: Waste product must be handled as a Flammable liquid.

**CONTAINERS:**

Empty containers may contain residual product. Caution: Residues are extremely flammable and will ignite with a source of ignition. Containers should be completely drained in a well ventilated area where vapours cannot accumulate and then stored until reconditioned or disposed of. Empty containers should be taken for recycling or disposal through suitably licensed contractors in accordance with Government regulations. As containers may contain extremely flammable residues, they should not be pressurised, cut by a grinder, drilled or exposed to heat, flames or other sources of ignition. Closed containers when exposed to such conditions/treatment may explode causing serious injury.

# SAFETY DATA SHEET

## SECTION 14 – TRANSPORT INFORMATION

This product is regulated for land, sea or air transportation. Limited quantities of 1L apply.

### 14.1 LAND (ADG Code):

**UN NUMBER:** UN1203  
**UN PROPER SHIPPING NAME:** PETROL.  
**TRANSPORT HAZARD CLASS(ES):** 3  
**PACKAGING GROUP:** II  
**ENVIRONMENTAL HAZARDS:** Marine Pollutant.  
**SPECIAL PRECAUTIONS FOR USER:** 243  
**HAZCHEM CODE:** 3YE

### 14.2 SEA (IMDG):

**UN NUMBER:** UN1203  
**UN PROPER SHIPPING NAME:** PETROL  
**TRANSPORT HAZARD CLASS(ES):** 3  
**PACKAGING GROUP:** II  
**ENVIRONMENTAL HAZARDS:** Marine Pollutant.  
**SPECIAL PRECAUTIONS FOR USER:** 243, 363 (EmS Statements: F-E, S-E) Warning: Flammable liquids

### 14.3 AIR (IATA):

**UN NUMBER:** UN1203  
**UN PROPER SHIPPING NAME:** PETROL.  
**TRANSPORT HAZARD CLASS(ES):** 3  
**PACKAGING GROUP:** II  
**ENVIRONMENTAL HAZARDS:** Marine Pollutant.  
**SPECIAL PRECAUTIONS FOR USER:** A100 (243) Warning: Flammable liquids

## SECTION 15 – REGULATORY INFORMATION

### 15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS: APPLICABLE REGULATIONS:

**SUSMP:** Schedule 5 (S5).  
**AIC:** All ingredients are on the AIC.  
**MONTREAL PROTOCOL:** Not applicable to this product.  
**STOCKHOLM CONVENTION:** Not applicable to this product.  
**ROTTERDAM CONVENTION:** Not applicable to this product.  
**BASEL CONVENTION:** Not applicable to this product.  
**INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM SHIPS (MARPOL):** Not applicable to this product.

# SAFETY DATA SHEET

## SECTION 15 – REGULATORY INFORMATION Continued

### OTHER REGULATORY INFORMATION:

#### GHS CLASSIFICATION HAZARD CLASS & CATEGORY

**AND HAZARD STATEMENT:** Flammable Liquids Category 1; H224 - Extremely flammable liquid and vapour.  
Flammable Liquids Category 3; H226 - Flammable liquid and vapour.  
Aspiration Hazard Category 1; H304 - May be fatal if swallowed and enters airways.  
Skin Corrosion/Irritation Category 2; H315 - Causes skin irritation.  
Specific Target Organ Toxicity (Single Exposure) Category 3; H336 - May cause drowsiness or dizziness.  
Chronic Aquatic Toxicity Category 2; H411 - Toxic to aquatic life with long lasting effects.  
Chronic Aquatic Toxicity Category 4; H413 - May cause long lasting harmful effects to aquatic life.  
AUH066 - Repeated exposure may cause skin dryness or cracking.

**HSNO APPROVAL NUMBER:** HRC000003.

**HSNO APPROVAL NAME:** Petrol (Unleaded).

## SECTION 16 – ANY OTHER RELEVANT INFORMATION

### SDS INFORMATION:

**Date of SDS Preparation:** 22<sup>nd</sup> March 2023

**Revision:** 1.4

**REVISION CHANGES:** Updated Product Code and to GHS 7 Classification Statements. Changes to Sections 1, 2, 3, 5, 8, 9, 10, 11, 12, 15 & 16.

### ACRONYMS:

SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
CAS Number	Chemical Abstracts Service Registry Number
EINECS	European Inventory of Existing Commercial Chemical Substances
UN Number	United Nations Number
OSHA	Occupational Safety and Health Administration
ACGIH	American Conference of Governmental Industrial Hygienists
HSE-WEL	Health and Safety Executive - Workplace Exposure Limit
EH40	EH40/2005 Workplace Exposure Limits
IMDG	International Maritime Dangerous Goods
IATA	International Air Transport Association
IUCLID	International Uniform Chemical Information Database
RTECS	Registry of Toxic Effects of Chemical Substances
%W/W	Percent weight for weight
OECD	Organisation for Economic Co-Operation and Development
ADG Code	Australian Code for the Transport of Dangerous Goods by Road and Rail
HAZCHEM Code	Emergency action code of numbers and letters which gives information to emergency services
NOHSC	National Occupational Health and Safety Commission
AICIS	Australian Industrial Chemicals Introduction Scheme
NICNAS	National Industrial Chemicals Notification & Assessment Scheme
IMAP	Inventory Multi-Tiered Assessment and Prioritisation
AIIC	Australian Inventory of Industrial Chemicals
TWA	Time-Weighted Average
STEL	Short Term Exposure Limit
HSNO	Hazardous Substances and New Organisms Act 1996
GHS	Globally Harmonised System of Classification and Labelling of Chemicals
WHS	Work Health and Safety PPE Personal Protective Equipment.
LD <sub>50</sub>	Median Lethal Dose
LC <sub>50</sub>	Median Lethal Concentration
EC <sub>50</sub>	Effective Concentration of a substance that causes 50% of the maximum response after exposure for a nominated time
NOAEL	No Observed Adverse Effect Level
NOEC	No Observed Effect Concentration

# SAFETY DATA SHEET

## SECTION 16 – ANY OTHER RELEVANT INFORMATION Continued

### ACRONYMS Continued:

ECHA	European Chemicals Agency
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
HCIS	Hazardous Chemical Information System
PBT	Persistent, Bioaccumulative and Toxic
vPvB	Very Persistent and Very Bioaccumulative

### LITERATURE REFERENCES AND SOURCES OF DATA:

OECD Guidelines for Testing of Chemicals  
Annex I: OECD Test Guidelines for Studies Included in SIDS  
Manual for the Assessment of Chemicals Chapter 2 Data Gathering  
International Toxicity Testing Guidelines  
Hazardous Chemical Information System (HCIS) - Guidance Material for Hazard Classifications  
Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.  
Model Work Health and Safety Regulations.  
Model Work Health and Safety Regulations - Transitional Principles  
Workplace Exposure Standards for Airborne Contaminants  
Australian Dangerous Goods Code 7<sup>th</sup> Edition  
Approved Criteria for Classifying Hazardous Substances [NOHSC:1008 (2004)]  
Guidance on the Classification of Hazardous Chemicals under the WHS Regulations  
Assigning a Hazardous Substance to a Group Standard  
User Guide to the HSNO Thresholds and Classifications  
Summary User Guide to the HSNO Thresholds and Classifications of Hazardous Substances  
Correlation between GHS and New Zealand HSNO Hazard Classes and Categories  
HSNO Control Regulations  
Record of Group Standard Assignment  
Labelling of Hazardous Substances Hazard and Precautionary Information  
Thresholds and Classifications Under the Hazardous Substances and New Organisms Act 1996  
Workplace Exposure Standards and Biological Exposure Indices  
NICNAS IMAP Human Health Tier II Assessment for Low Boiling Point Petroleum Naphthas including CAS Number: 68527-27-5

All information contained in this Safety Data Sheet and the health, safety and environmental information are considered to be accurate to the best of our knowledge as of the issue date specified above. The information presented here within, is based upon the product information supplied by the manufacturer. However, no warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this data sheet.

Health and safety precautions and environmental advice noted in this data sheet may not be accurate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The Company accepts no responsibility for any injury, loss or damage, resulting from abnormal use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material.